



TECHNICAL CHART 41

# GRASSELLO EVOQUE

## Description of product

Very fine "Grassello Paste" for prestigious shiny finishing with Venetian Stucco effect.

## Application Field

Prestigious high shiny decorations for interiors.

## Product characteristics

GRASSELLO EVOQUE is a prestige product composed of very fine, micro-filtered lime putty. The feature that differentiates it from the product "Grassello Lucido" is about the possibility to be applied in thicker layers. The application cycle becomes faster with the possibility to complete works in less time with exceptional results. The colour shades can be personalized by using the colour scheme of the Tintometric system Luxury&Lime. The accurate mixture with selected micro-marble produces a stucco in paste, ready to be used, which permits a vast range of application methods able to satisfy the most sophisticated decorating requests. The tradition of lime, produced with an advance technology, aims Bericalce towards the Environment Care and Green Division market. The natural raw materials, accurately selected, give GRASSELLO EVOQUE a very high ecologic value: the dispersion of humidity avoids the growth of moulds and bacteriums, without using chemical additives. Non-flammable and low odour.

Technical data	
Name	Grassello Evoque
Composition	Slaked "micronized" lime(Grassello) minimum 12 months aged, marble powders and additives for less than 5%.
Aspect	Highly dense paste
Color	Natural White
Dilution	Ready to use (if needed a dilution in water 0-5%)
Quantity per layer	ca. 4 - 5 m <sup>2</sup> /Kg
PH	13
Vapour permeability	SD - 0,04m (DIN 52615)
Water absorption	w - 0,3kg / (m <sup>2</sup> h0,5) (EN1062-3:2001)
VOC class	VOC 5g/l - wall paint and subcategory "L" max.value UE2010 30g/l
Specific weight	1,45 kg/litre
Packaging	5 - 22,5 kg buckets
Storage	Keep in dry place with temperture min.5° - 30°C max.
Notice	Protect the surfaces during the 12 hours after application

# **GRASSELLO EVOQUE**

---

## **Instructions for use**

- Prepare the base with a specific Primer, Isolante Acrilico or smoothing base like Micro Primer Veneziano of Bericalce
- Application with stainless steel trowel
- Base must be clean and dry, any unsubstantial parts, traces of oil or grease must be removed; plaster any irregularity of the base.
- Apply 2 coats or more. An additional procedure will be done to refine the grade of brightness after application, by using a trowel and/or special tools. The product can be applied and finished in only one day. Only warning is that between the various drafts the applied product is dry enough.
- Temperature of application: 5° to 30°C
- All lime-based products have a normal drying time according to the thickness but, the real hardness is obtained through carbonation which occurs on contact with the air.  
This process could last many months

## **Notes**

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

**Date of issue 01.04.2004**

## **BeriCalce ITALIA**

Via Odorico da Pordenone, 18

36100 Vicenza - ITALY

Phone (+39) 0444 929102

Fax (+39) 0444 929102

Skype: bericalce

info@bericalce.com

**bericalce.com**